

ZOFFANY

TRUE MATT

DESCRIPTION
Fast drying, fabulously flat and environmentally friendly, Zoffany True Matt is a water based emulsion that combines irresistible chalky looks with a washable finish.

Perfect for walls and ceilings, this transformative paint is quick drying, enveloping interiors in Zoffany's signature style. Visible brush strokes and cutting in are reduced and intense pigments provide an incredible depth of colour.

KEY PROPERTIES
- Dries flat in two hours, leaving a luxurious, high performance finish
- Washable and environmentally friendly
- Excellent scrub resistance and good resistance to marring for its sheen level
- Ideal for high traffic areas such as hallways and kitchens
- Self-priming on most surfaces

PREPARATION
All surfaces to be painted should be clean, dry and free from loose and flaking material including dirt and grease. Prime bare metal surfaces with an appropriate primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust and wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces as they may contain harmful lead.

APPLICATION
Stir well before use. Ensure good ventilation during application and drying. Apply by brush, roller or sprayer. Do not overfill paint trays. Ensure roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading. Apply two coats. Additional coats may be required on new plaster or where a greater colour change is desired. Do not apply in temperatures below 10ºC or in damp conditions. If more than one can of colour is to be used in the same area, intermix before use.

CLEANING
Remove as much product as possible from equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

HEALTH & SAFETY
- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-octyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one. May produce an allergic reaction. Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. Safety data sheet available on request.

RECOMMENDED USES
Suitable for commercial and residential spaces.

TYPE OF SUBSTRATE
Interior walls, ceilings, woodwork, suitably prepared metal and radiators.

COLOUR RANGE
Alchemy of Colour collection, 156 colours.

FINISH
Minimal sheen - 2%.

VOLUME SOLID
35.2%.

COVERAGE
One coat of Zoffany True Matt covers up to 14m2 per litre, depending on the nature and porosity of the surface.

DRYING TIME
Touch dry in 1 - 2 hours. Recoatable after 2 - 4 hours.

TRANSPORTATION & STORAGE
To avoid the risk of spillage, always store and transport in a secure upright position.
Protect from frost, store away from heat and flame.

CLEANER
Clean water.

VOC CONTENT
- Low VOC (Volatile Organic Compounds) Content 0.3 -7.99%.
- EU limit value for this product Cat A/(a): 30 g/L (2010).
- This product contains max 8g/l VOC.

FILM THICKNESS
Wet: 86μm, Dry: 30μm.

SIZES
2.5 Litre, 5 Litre.