

# ANDREW MARTIN

## GLOSS FINISH PAINT

### DESCRIPTION

Gloss is an ultra-tough, light reflecting paint with the ease of handling and convenience of a pure acrylic, water-based paint. Surfaces are washable and have high scrub and mould growth resistance making it the perfect gloss paint for all internal and external surfaces, including high traffic areas and those where high levels of moisture and grease are a challenge. Unlike traditional oil based gloss paints this product will not fade and no undercoat is required on previously painted surfaces. It can also be used as a mist coat for sealing new plaster, plasterboard and jointing compound prior to applying top coats. This means one product is all you need and therefore saves labour and product costs.

### TYPICAL USES

- Interior and exterior timber surfaces.
- High use interior surfaces and where regular cleaning and washing down is necessary for hygiene
- Metal radiators and surfaces (with appropriate metal primer on bare substrates)

### PHYSICAL PROPERTIES

- Sheen Level\* – 80%
- Coverage – up to 20 square metres per litre per coat (varies with substrate and texture)
- Recommended dry film thickness – 30 microns per coat
- Recommended number of coats – 2
- Touch dry and recoat time – between 20 minutes and 1 hour (dependant on atmospheric conditions)
- Scrub resistance – Class 1
- Volume solids – 40%
- Colour availability – any colour
- Tin sizes – 1, 2.5 and 5 litres
- Odour – virtually zero

\*Final sheen level is given based upon two full coats being applied

### ENVIRONMENT

- 2010 maximum permitted limit grams per litre – 130g/l
- VOC category for this product – d
- Actual VOC content grams per litre – 45 g/l
- Classification – minimal

### HEALTH & SAFETY

Our products are designed to cause no harm. Detailed safety information is available on our website or on request.

### SURFACE PREPARATION

Ensure that surfaces are free from dirt, dust, grease, mould and any other contaminants that may affect adhesion. Clean off any surface mould with anti-fungicidal cleaner and rinse off. Contaminated areas should be washed down thoroughly with sugar soap and rinsed off. Once cleaned, lightly sand surface to form a key and then clean with a lint free cloth. Imperfections and loose flaking paint should be sanded to remove as required, and all dry painted edges feathered off to a smooth finish.

Holes, impressions and cracks must be filled with proprietary surface fillers as required. Powdered fillers such as Tetrion, Polyfiller or similar are not recommended. For best results use Easifill, Red Devil, Onetime or two pack fillers for wood. Spot prime all surface fillers with A quality acrylic all purpose primer before the application of top coats.

#### New timber surfaces

For soft wood, knots should be treated with a proprietary knotting solution to prevent bleed through. Ensure that the wood is completely dry. A suitable, quality primer is necessary for exterior timber surfaces prior to applying the top coat. For interior timber Andrew Martin Matt or Low Sheen can be applied as a primer instead.



# ANDREW MARTIN

## Timber surfaces previously painted with acrylic paint and alkyd paint

No undercoat is required when correct preparation has been completed. Clean and sand lightly to provide a key to aid adhesion. Plastics Clean and lightly sand to provide a key followed by an application of a suitable, quality primer before applying top coats. Bare ferrous and non-ferrous metal surfaces Clean to remove any grease or contaminants. Apply a proprietary metal primer before applying top coats.

## APPLICATION

This product can be applied in temperatures between 5°C and 30°C. Take care to avoid contact with the painted surface before the product has been able to dry. Always follow the touch dry and recoat times stated above.

### Brushing

Use only high-quality synthetic brushes suitably sized for the job in hand. Ensure that brushes are sufficiently dry after washing out before use. Apply paint generously with even brush strokes maintaining a wet edge as you progress leaving the paint to find its own level. Do not overwork and take care not to brush over paint that has already started to dry.

### Roller

Use only short napped synthetic rollers for the best result on smooth surfaces. The nap length can be increased for textured surfaces as required. Take care to maintain a wet edge and to avoid lapping marks and flashing. Never over roller paint that has started to dry.

### Spray application

For airless spray application, dilute paint by 25%. Use tip sizes and pressure based upon the job in hand. In all instances, seek technical guidance from the manufacturers of the spray equipment.

## CLEAN UP & DISPOSAL

Remove excess paint from all equipment. The cleaning of brushes and rollers should be carried

out immediately using clean water. Cleaning is most effective if the water is slightly warm.

## STORAGE & SHELF LIFE

To avoid risk of spillage, always store and transport in a secure upright position.

Storage of paint should be in a cool dry and frost-free environment, away from direct heat and sunlight.

Products that are unopened can be stored at least two years and containers which are opened must be free of contaminants and should be properly resealed and kept upright.

All products will need to be stirred thoroughly prior to use following extended periods of time in storage.

## LIFE CYCLE MAINTENANCE

### Cleaning

Remove stains and marks using a clean cloth, water and a detergent such as washing up liquid.

### Touching in

Whilst this is generally not recommended for perfect results, both marks that cannot otherwise be cleaned, and small repairs using fillers, can be satisfactorily touched in, provided that fillers are sealed with a primer or mist coat first. For best results, the method of original paint application should be used to carry out any touching in.

